



(19)

Generated Document.

(11) Publication number: **09155524 A****PATENT ABSTRACTS OF JAPAN**(21) Application number: **07314078**(51) Int. Cl.: **B22D 17/20**(22) Application date: **01.12.95**

(30) Priority:	(71) Applicant: <b>JAPAN STEEL WORKS LTD:THE</b>
(43) Date of application publication: <b>17.06.97</b>	(72) Inventor: <b>KIHARA YUJI NAGAWA AKITAKA TAKEYA KENGO MATSUI SHINJI</b>
(84) Designated contracting states:	(74) Representative:


**(54) METHOD AND DEVICE  
FOR TAKING OUT SCREW  
OF INJECTION MOLDING  
MACHINE**

(57) Abstract:

**PROBLEM TO BE SOLVED:** To prevent ignition and combustion of a molten light alloy material stuck to a screw, in taking out the screw from an injection molding machine, by extruding the screw into a cylindrical metallic container with an inactive gas as an atmosphere gas.

**SOLUTION:** In taking out a screw 2 from a cylinder barrel 1 using a screw drawing jig, a cylindrical metallic container 5 is arranged which is hung at the tip end of the cylinder barrel 1 by means of a crane or the like, with the screw 2 extruded into this container 5. In this case, an inactive gas is supplied from its source 6 in the cylindrical metallic container 5 through a flow rate regulating valve 9 and a piping 7. Consequently, the ignition and combustion are prevented of an injection light alloy material which is stuck to the screw 2 and which is in a molten state, thereby eliminating the lowering of the mechanical characteristics of the screw material and enabling the drawing operation to be performed safely for the screw.

COPYRIGHT: (C)1997, JPO



**THIS PAGE BLANK (USPTO)**